

Rubber Flooring > Acoustic > Soundproof Underlay

High-Density Acoustic Rubber Underlay | Up to 78 dB Impact & Airborne...



Professional Acoustic Rubber Underlay - Engineered for Maximum Sound Insulation Performance Specify with confidence.

TECHNICAL SPECIFICATIONS

Material	High-density recycled rubber
Impact Noise Reduction	Up to 78dB
Airborne Noise Reduction	Up to 42dB
Density	550-750 kg/m3
Temperature Range	-20C to +60C
Compliance	BS EN ISO 10140, REACH

AVAILABLE OPTIONS

Size	1.5mm Thick x 1.25 meters Width, 2mm Thick x 1.25 meters Width, 3mm Thick x 2.0 meters V
------	--

HOW TO ORDER

Website	www.slip-not.co.uk/products/acoustic-soundproof-rubber-underlay-linear-metre-high-density-barrier-mat-
Email	sales@slip-not.co.uk
Delivery	Free UK Delivery on all orders
Trade Accounts	Bulk pricing available - contact us for a quote

All specifications are typical values for guidance only. Slip-Not.co.uk reserves the right to amend specifications without notice. For critical applications, we recommend ordering a sample for independent testing prior to purchase. TDS-SN-2026.